


# DP2K-6E

Compact DLP Barco Alchemy Cinema projector for screens up to 7.5m (24ft) wide



## Taking digital cinema where it's never gone before

The largest digital cinema projector portfolio in the world is proud to present its latest family member: the DP2K-6E. This brand-new model brings compact, fully integrated and DCI compliant digital cinema projection to small and independent cinemas worldwide. And how!

## Why you'll love the DP2K-6E

- Cost-effective and fully integrated thanks to its on-board Barco Alchemy Series 3 module
- UHP lamps enable easy maintenance and compact design
- Twice as silent as the quietest projector currently on the market and super compact
- Trademark Barco quality, and modularity, now also for the smallest screens

**BARCO**

Visibly yours

**Product specifications****DP2K-6E**

<b>Digital MicroMirror Device™</b>	3 x 0.69" DC2K dark metal devices
<b>Native resolution</b>	2,048 x 1,080 pixels
<b>Housing</b>	Hermetically sealed DMDs and optical assembly
<b>Light output</b>	DCI colors: 4,800 lumens Non-DCI: 7,200 lumens
<b>Lamps</b>	Dual 465W, UHP lamps
<b>Screen size</b>	Up to 7.5m/24.6 ft wide (screen gain 1.2 @ 14ftl)
<b>Contrast ratio</b>	1,500:1
<b>Prime lenses</b>	Fully motorized 1.2 - 1.7 1.34 - 1.9 1.5 - 2.15 1.7 - 2.55 2.0 - 3.9
<b>Control I/O</b>	3x Ethernet (RJ 45) 8x GPIO (DB 25) 3D interface USB interface
<b>Integrated Cinema Media Processor</b>	JPEG2000 2K & 4K DCI play-out High Frame Rates 3D up to 120fps (60fps per eye) JPEG 2000 bit-rates up to 625Mbps Dual-channel color-correction MPEG-2 (4:2:0 and 4:2:2 up to 60fps) H.264** 2x DisplayPort 1.1a 2x 3G-SDI inputs* 1x HDMI 1.4a input 2D and PCM audio / 4K 24fps (BluRay HD 3D on roadmap)* 16x AES/EBU audio channels (2x RJ45) 8x GPI, 8x GPO (4x RJ45) 2x ETH for content connectivity & ingest 2x front-accessible USB 3.0 for fast ingest 2x front-accessible USB 2.0 Video watermarking: Civolution NexGuard Audio watermarking: Civolution Closed captioning devices: Support for SMPTE 430-10 *optional for China ** software roadmap
<b>Integrated storage</b>	1.9TB effective storage (RAID-5) 3x 1TB Hot-swappable 2.5" hard-drives
<b>Barco Web Commander</b>	Projector Dashboard Projector Control Board Show Player/Editor/Scheduler Automation, 3D, Ingest TMS integration Smart Projector Status Via HTML5 web-browsers including iOS & Android tablets
<b>Barco Communicator</b>	Projector installation & configuration Projector update & maintenance
<b>Power requirements</b>	200-240 VAC
<b>Projector dimensions (HxWxD)</b>	369 x 689 x 664 mm 14.5 x 27.1 x 26.1 inch
<b>Projector weight</b>	Recessed handles for easy carrying 53.8 kg / 119 lbs
<b>Ambient temperature</b>	35°C / 95°F Max.
<b>Options</b>	Barco CineMate App (iOS & Android) - free 3D add-ons Touch screen monitor, inc. Barco Commander & Communicator Pedestal CineCare Web Auro 11.1 license Live 3D*** Ghostbusting*** Ceiling mount kit*** *** roadmap
<b>Noise Level</b>	48 dB(A)

**Product specifications**

**DP2K-6E**

**Airflow requirements**

43 CFM

Last updated: 30 jun 2015  
Technical specifications are subject to change without prior notice.  
Please check [www.barco.com](http://www.barco.com) for the latest information.

**BARCO**

Visibly yours